


156 Series Monocrystalline Solar Module

230W -240W



High Module Conversion Efficiency (Up to 14.75%)



Easy Installation and Handling for Various Applications



Strong Wind-pressure(2400Pa) & Snow Load (5400Pa)



Conform with PV Standards: IEC61215, IEC61730 and UL1703




QC System: ISO9001:2008

Warranty


5 Years Manufacturing Warranty

10 Years Warranty, 90% Power Output


25 Years Warranty, 80% Power Output



Dimension of PV Module JCS-24/Bb



I-V Curves of PV Module JCS-24/Bb



Packing Information

Container	20'GP	40'GP	40'HQ
Pieces per Pallet	20	20	22
Pallets per Container	12	28	29
Pieces per Container	240	560	616

Electrical Data at STC

	JC230S-24/Bb	JC235S-24/Bb	JC240S-24/Bb
Maximum Power (Pmax)	230W	235W	240W
Power Tolerance	±3%	±3%	±3%
Efficiency of Module	14.14%	14.44%	14.75%
Optimum Operation Current (Imp)	7.90A	8.02A	8.11A
Optimum Operation Voltage (Vmp)	29.1V	29.3V	29.6V
Short Circuit Current (Isc)	8.03A	8.17A	8.32A
Open Circuit Voltage (Voc)	38.3V	38.4V	38.4V

Values at Standard Test Conditions STC (Air Mass AM1.5, Irradiance 1000W/m², Cell Temperature 25°C)

Temperature Rating

Temperature Coefficient of Voc	-0.36%/ °C
Temperature Coefficient of Isc	0.03%/ °C
Temperature Coefficient of Pmax	-0.53%/ °C
Nominal Operating Cell Temperature (NOCT)	45 °C

General Data

Cell Type	156 x 156mm Monocrystalline, 60(6x10) pcs in series
Glass	High Transmission, Low Iron, Tempered Glass 4mm
Frame	Anodized Aluminum Alloy, 20 Draining Holes in Frame
Junction Box	TUV Certified, IP65 rated connector

Mechanical Configuration

Dimension	1640x992x50mm
Installation Hole Dimensions	1360x860x947mm
Cable Length	900mm
Weight	23Kg

Maximum Ratings

Operating Temperature	-40 ~ +85°C
Storage Temperature	-40 ~ +85°C
Maximum System Voltage	1000V (IEC) / 600V (UL)
Number of Bypass Diodes	6pcs
Maximum Series Fuse	20A